

# PA2200

Tough functional prototype material  
suitable for snap fits/ living hinges



## Applications

- Tough, functional prototype models
- Suitable for under bonnet applications
- High temperature resistant (up to 150°C)
- Suitable for snap fits/living hinges



## Physical Properties

Colour	White
Type	Nylon

## Mechanical Properties

		TEST/ISO
Hardness Shore A/D	<b>75D ± 2</b>	DIN 53505
Flexural Modulus (MPa)	<b>1,240 ± 130</b>	DIN EN ISO178
Tensile Strength (MPa)	<b>45 ± 3</b>	Din EN ISO527
Tensile Modulus (MPa)	<b>1,700 ± 260</b>	
Elongation Break (%)	<b>20 ± 5</b>	
Impact Strength (J/m)	<b>32.8 ± 3.4</b>	DIN EN ISO180

## Thermal & Specific Properties

Melting Point (°C)	<b>172 – 180</b>	DIN 53736
--------------------	------------------	-----------

Call: 028 9070 6940  
Email: [sales@laserproto.com](mailto:sales@laserproto.com)  
Web: [www.laserproto.com](http://www.laserproto.com)

[Click here to request a quote](#)

Please be advised that all information provided in this document is representative of typical properties and as advised by the material manufacturer. Performance characteristics of these products may vary according to product application, operating conditions or with end use.

Laser Prototypes Ltd makes no warranties of any type, express or implied, with respect to any of the goods or services supplied. This includes but is not limited to any warranty of fitness for a particular purpose or of properties or of suitability for a specific application. Data are subject to change without notice as part of our continuous development and improvement processes.